

Cabinets, Racks and Accessories

Floor Standing Cabinets SRS 19"

01



Floor Standing Cabinets SRS - Standard

Features:

- sheet steel housing with welded frame, completely pre-assembled, self ventilated,
- surface finish: powder painted in RAL 7035 - light grey (other colors on request),
- protection IP20 in accordance with PN 92/E-08106/EN 60529/IEC 529. (does not apply to brush cable entries),
- indoor use,
- cabinets can be arranged in line using line-up bolts after removing side walls (Part No. ZLS),
- cabinet frame fully welded - 1,5 mm thick sheet steel on 4 x leveling feet M10,
- front door: window made of safety glass (optionally: full steel, full glass, punched perforated plate), opening angle 180 degrees. Left or right door opening options,
- cabinet rear panel - 1 mm. thick sheet steel, removable with two single point locks (Optionally: full steel or perforated, left or right side mounted door),
- cabinet side panels - 1 mm thick sheet steel, removable with two single point locks,
- two pairs of the profile rails (AL-Zn coated) each arranged at the front and rear on the inside. Each profile with unit labeling,
- possibility to increase maximum weight of equipment mounted in the cabinet SRS by using cabinet max load strengthen kit,
- cables let in entry optionally either from roof or base, either, through top or bottom of the rear side of cabinet, pre-punched opening. (Dimensions: 450 x 90 mm),
- in the roof and base of cabinet 2 x 4U blind plates (pre - punched opening) for fan units (possible configurations 1 or 2 x 2 fan units, 1 x 4 fan units 1 x 6 fan units),
- wide range of supplementary accessories: plinths, shelves, fan units, light units, power distribution units, blanking covers, cable management, accessories etc,
- optional 19" swing frame 90° opening.

Type	Dimensions (mm)			Weight (kg)	Load capacity (kg)	Index
	Width	Depth	Height			
15U	600	600	780	44	300	SRS-15-6/6-S01-G
	600	800		51		SRS-15-6/8-S01-G
	800	800		60		SRS-15-8/8-S01-G
	800	900		64		SRS-15-8/9-S01-G
18U	600	600	915	48	300	SRS-18-6/6-S01-G
	600	800		56		SRS-18-6/8-S01-G
	800	800		64		SRS-18-8/8-S01-G
22U	600	600	1095	53	300	SRS-22-6/6-S01-G
	600	800		62		SRS-22-6/8-S01-G
	800	800		71		SRS-22-8/8-S01-G
	800	900		76		SRS-22-8/9-S01-G
24U	600	600	1210	82	300	SRS-24-6/6-S01-G
	600	800		82		SRS-24-6/8-S01-G
	800	800		82		SRS-24-8/8-S01-G
	800	1000		82		SRS-24-8/10-S01-G
27U	600	600	1315	60	300	SRS-27-6/6-S01-G
	600	800		69		SRS-27-6/8-S01-G
	800	800		80		SRS-27-8/8-S01-G
32U	600	600	1535	73	400	SRS-32-6/6-S01-G
	600	800		87		SRS-32-6/8-S01-G
	600	900		88		SRS-32-6/9-S01-G
	800	800		102		SRS-32-8/8-S01-G
	800	900		108		SRS-32-8/9-S01-G
42U	600	600	1980	88	400	SRS-42-6/6-S01-G
	600	800		105		SRS-42-6/8-S01-G
	800	600		103		SRS-42-8/6-S01-G
	600	900		110		SRS-42-6/9-S01-G
	800	800		121		SRS-42-8/8-S01-G
45U	600	600	2120	92	400	SRS-45-6/6-S01-G
	600	800		109		SRS-45-6/8-S01-G
	800	800		127		SRS-45-8/8-S01-G

Accessories supplied:

- 1 x brush terminal,
- 1 x set of captive nuts (16 pcs.),
- 2 x keys for sides and rear panels,
- 2 x keys for front door,
- 4 x leveling feet M10,
- 1,5 m of special cable entry cover for cables protection (after re-moving cable entry).

